



Typical Performance

Parameter	Value
'HWHFWRU)RUPDW	[wP SL[HO
6HQVLQJ 0DWHULDO	;%Q RSHUDWLQJ DW .
,QWHJUDWLRQ 0RGHV	,75 ,:5
,QWHJUDWLRQ &DSDFLWRUV	0H 0H
2SHUDWLRQ 0RGHV)XOO ,PDJH 3URFHVVVLQJ 0RGH 9LGH 5DZ 'LJLWDO RXWSXW 3UR[\ 0RGH
9LGHR (QJLQH 0DLQ 3URFHVVVLQJ \$OJLWLRQV ,PDJH (QKDQFHPHQW DQG 'LJLWDO 3VHXGR FRORU *UDSKLFV	188.0%35
0D[LPXP)UDPH 5DWH	+] ZLWK ,PDJH 3URFHVVVLQJ +] ZLWKRXW ,PDJH 3URFHVVVLQJ
'LJLWDO 6LJQDO 5HVROXWLRQ	ELW
1(7' 0H FDSDFLWRU	P. # ZHOO ILOO FDSDFLW\
5HVLGXDO 1RQ 8QLRUPLW\	67' '5 DW ZHOO ILOO FDSDFLW\
2SHUDELOLW\	!
, '&\$ 2SWLFDO 3DUDPHWHUV	6WDQGDUG) 6SHFWUDO 5DQJH K ŠP
&RROHU 7\SH	0LFUR &RROHU 6SOLW /LQH DU
0RGXOH 07%)	! KRXUV *0 # r&
0RGXOH 7RWDO 3RZHU &RQVXPSWLRQ # 18	7\SLFDO : QRW LQFOXGLQJ ,PDJH 3URFHVVVLQJ \$GGLWLRQDO : '& IRU IXOO YLGH R SU
,PDJH 5HDG\ # r&	7\SLFDO PLQXWHV
0RGXOH 'LPHQVLRQV	[[PP P [P [P
0RGXOH :HLJKW	JP OE
6SHFLILFDWLRQV DUH VXEMHFW WR FKDQJHV ZLWKRXW IXUWKHU QRWLFH	

